


Data Sheet

Hook Up Wire

LifK4 1 x 0,25 / 0,95



CONSTRUCTION:

Conductor: Stranded copper wire, 128 x 0,05 mm => 0,25 mm², bare,

Insulation: TPE-E (K4)
 Colour : optional
 Ø : 0,95 ± 0,05 mm
 Shorehardness (D) : 72 ± 2

Technical Data:

Test voltage : > 0,5 kV
 at 50 Hz eff. for 1 minute.
 Insulation resistance min. : 20 MOhm x km at 20 °C
 Conductor resistance max. : 78 Ohm/km at 20 °C
 Operating voltage max. : 50 V
 Temperature rating:
 static : - 50 to + 120 °C
 operating : - 40 to + 120 °C
 Current max. : 5 A at 25 °C ambient temperature

B	Conductor: old: 4x32x0,05	20.07.2011	J. Puff
A	updated	24.11.2008	J. Puff
	Revision:	Date:	Name:
X	first edition	09.12.2001	J. Puff

The information provided in this data-sheet is correct according to the best of our know-ledge. It is provided for information purposes only and is intended to assist with planing. It does not relieve the user of his or her responsibility to check in advance whether the products we supply are suitable for the purpose intended by the user. It is subject to change, should new information render this necessary.