


Product Area	Male socket, solder M16 connectors IP 40	serie 581/ 680/ 682	Pole Article number	5 09 0315 00 05
--------------	---	---------------------	---------------------	--------------------


illustration



scale drawing



Contact Arrangement



	X	Y
1	3,03	-1,75
2	3,03	1,75
3	0,00	3,50
4	-3,03	1,75
5	-3,03	-1,75

You can find the assembly instruction on the next page.

Technical data

Common values

Connector Design	Male socket
Connector locking system	Screw
Termination	solder
Wire gauge (mm)	0,75 mm <sup>2</sup>
Wire gauge (AWG)	20
Upper temperature	+85 °C
Lower temperature	-40 °C

Material

Material of contact	CuZn (brass)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)
Material of housing	zinc diecasting, nickel plated

Cable data

Contacts 5, male socket, solder, silver plated contacts

Electrical values

Rated voltage	250 V
Rated impulse voltage	1500
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	6 A
Volume resistivity	≤ 5 mΩ
EMV compliance	shielded
Degree of protection	IP 40
Mechanical operation	>500 mating cycles



Product  
Area

Male socket, solder  
M16 connectors IP 40

serie 581/ 680/ 682

Pole  
Article number

5  
09 0315 00 05

Installation instructions / Mounting cutout

