

Item no.: 256-401  
 Product description: MODULAR PCB TERMINAL BLOCK; 2 SOLDER PINS / POLE; 1 POLE; PIN SPACING 5/5.08 MM / 0.2 IN; FRONT-ENTRY; CAGE CLAMP®CONNECTION



Packing unit 600 6\*100 pieces

Pin spacing from	5 mm
Pin spacing up to	5,08 mm
Pin spacing from	0,197 in
Pin spacing up to	0,2 in
pole count	1
Cross section from [mm <sup>2</sup> ]	0,08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2,5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage UL	300 V
Voltage CSA	300/600 V
Current UL	15 A
Current CSA	15/5 A
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	16 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	16 A
Weight	0,94 g
Color	grey
Wiring type	Angled Type
No. of connection Points	1
No. of potentials	1
Height	18,2 mm
Height	0,72 in
Width	5 mm
Width	0,197 in
Depth	17,6 mm
Depth	0,693 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0,22 in

Admission office

Approval no.

Voltage  
[ V ]

Current  
[ A ]

Cross section  
[ mm<sup>2</sup> ]

256-401	BBJ	B/12/697/03	250	16	0,5-2,5
256-401	BV	11915/A0	500/250	16	0,08-2,5
256-401	CCA	DK2082	250	16	0,5-2,5
256-401	CSA	18677-45	300/600	15/5	28-12
256-401	CSM	017956	500/1000	16	0,08-2,5
256-401	DEMKO	98-04355	250	16	0,5-2,5
256-401	DNV	E6998	500/250	16	0,08-2,5
256-401	GL	17296-00HH	500/250	16	0,5-2,5
256-401	KEMA	93.9001.01	380		2,5
256-401	RMR	99.00007.250	250	16	0,5-2,5
256-401	RosTesT	B09523	250/500	16	0,08-2,5
256-401	UL	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected