

Item no.: 257-857
 Product description: MODULAR PCB TERMINAL BLOCK; 2
 SOLDER PINS / POLE; 1 POLE; PIN
 SPACING 7.5/7.62 MM / 0.3 IN; ANGLED
 LEVER; FRONT-/SIDE-ENTRY



Packing unit 400 4*100 pieces

Pin spacing from	7,5 mm
Pin spacing up to	7,62 mm
Pin spacing from	0,295 in
Pin spacing up to	0,3 in
pole count	1
Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	2,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage UL	300 V
Current UL	15 A
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	16 A
Measured voltage EN	800 V
Measured shock voltage	6 kV
Pollution degree	2
Current intensity EN	16 A
Weight	1,357 g
Color	light green
Wiring type	Front-/Side-entry
No. of connection Points	1
No. of potentials	1
Height	20,2 mm
Height	0,795 in
Width	7,5 mm
Width	0,295 in
Depth	14,2 mm
Depth	0,559 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0,22 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
257-857	BBJ	B/12/697/03	400	16	0,5-2,5
257-857	BV	11915/A0	800/400	16	0,08-2,5

257-857	CCA	DK2082	400	16	0,5-2,5
257-857	CSM	017956	400/800	16	0,08-2,5
257-857	DEMKO	98-04355	500	16	0,5-2,5
257-857	DNV	E6998	800/400	16	0,08-2,5
257-857	GL	17296-00HH	800/400	16	0,5-2,5
257-857	RMR	99.00007.250	400	16	0,5-2,5
257-857	RosTesT	B09523	400/800	16	0,08-2,5
257-857	UL	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected