

Item no.: 280-101  
 Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK; LATERAL MARKING; CARRIER RAIL DIN 35; SIDE-ENTRY; CAGE CLAMP®CONNECTION; HORIZONTAL TYPE



Packing unit 100 pieces

Cross section from [mm <sup>2</sup> ]	0,08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2,5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current UL	20 A
Current CSA	20 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	3,935 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	30,5 mm
Height	1,2 in
Width	5 mm
Width	0,197 in
Depth	42,5 mm
Depth	1,67 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm <sup>2</sup> ]
280-101	BBJ	B/12/700/03	800	24	2,5
280-101	BV	07436/Co	800	24	2,5
280-101	CCA	NL4912	800	24	2,5
280-101	CSA	154112-1536071	600	20	28-12
280-101	CSM	017956	800	24	2,5
280-101	DEMKO	78571	750		2,5
280-101	Dep.MaE	CS4865N	600	25	2,5
280-101	DNV	E6999	800	24	2,5
280-101	GL	17295-00HH	800	24	2,5
280-101	KEMA	98.2759.03	800	24	2,5
280-101	KR	HMB05880-EL001	800	26	2,5

280-101	LCIE	218194	750		2,5
280-101	LR	91/20112(E1)	800	24	2,5
280-101	NEMKO	M52726/01	750		2,5
280-101	PRS	TE/1219/880590/98	800	24	2,5
280-101	RMR	99.00007.250	800	24	2,5
280-101	RosTesT	B09523	800	24	2,5
280-101	SABS	ED751/8188	750		2,5
280-101	SABS-EX	?e?741/85712/W491	550	24	
280-101	UL	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected