

Item no.: 280-641
 Product description: 3-CONDUCTOR THROUGH TERMINAL BLOCK; CENTRE MARKING; CARRIER RAIL DIN 35; FRONT-ENTRY; CAGE CLAMP®CONNECTION; ANGLED TYPE



Packing unit 100 pieces

Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	2,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current UL	20 A
Current CSA	25 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	6,68 g
Color	grey
Wiring type	Angled Type
No. of connection Points	3
No. of potentials	1
Height	36,5 mm
Height	1,44 in
Width	5 mm
Width	0,197 in
Depth	50,5 mm
Depth	1,99 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
280-641	BBJ	B/12/700/03	800	24	2,5
280-641	BV	07436/Co	800	24	2,5
280-641	CCA	NL4912	800	24	2,5
280-641	CSA	154112-1536071	600	25	28-12
280-641	CSM	017956	800	24	2,5
280-641	DEMKO	78571	750		2,5
280-641	Dep.MaE	CS4865N	600	25	2,5
280-641	DNV	E6999	800	20	2,5
280-641	GL	17295-00HH	800	24	2,5
280-641	KEMA	98.2759.03	800		2,5
280-641	LR	91/20112(E1)	800	24	2,5

280-641	NEMKO	L92359	750		2,5
280-641	PRS	TE/1219/880590/98	800	24	2,5
280-641	RMR	99.00007.250	800	24	2,5
280-641	RosTesT	B09523	800	24	2,5
280-641	UL	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected