

Item no.: 282-104
 Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK; LATERAL MARKING; SUITABLE FOR EEX I APPLICATIONS; CARRIER RAIL DIN 35; SIDE-ENTRY; CAGE CLAMP®CONNECTION



Packing unit 50 pieces

Cross section from [mm ²]	0,2 mm ²
Cross section to [mm ²]	6 mm ²
Cross section from [AWG]	24 AWG
Cross section to [AWG]	10 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current UL	30 A
Current CSA	40 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	41 A
Weight	11,286 g
Color	blue
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	37 mm
Height	1,46 in
Width	8 mm
Width	0,315 in
Depth	46,5 mm
Depth	1,83 in
Strip length from	12 mm
Strip length to	13 mm
Strip length	0,49 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
282-104	BBJ	B/12/700/03	800	41	6,0
282-104	BV	07436/Co	800	41	6,0
282-104	CCA	NL5448	800	41	6,0
282-104	CSA	154112-1505033	600	40	24-10
282-104	CSM	017956	800	41	6,0
282-104	DEMKO	78012	750		6
282-104	Dep.MaE	CS4867N	600	40	6
282-104	DNV	E6999	800	41	6,0
282-104	GL	17295-00HH	800	41	6

282-104	KEMA	98.2759.05	800		6
282-104	KR	HMB05880-EL001	500/800	10-46	6
282-104	LCIE	218194	750		6
282-104	LR	91/20112(E1)	800	41	6,0
282-104	NEMKO	M52728	750		6
282-104	PRS	TE/1219/880590/98	800	41	6,0
282-104	RMR	99.00007.250	800	41	6,0
282-104	RosTesT	B09523	800	41	6,0
282-104	SABS	ED751/8190	750		6
282-104	UL	E45172	600	30	24-10

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected