

Item no.: 283-101
 Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK; LATERAL MARKING; CARRIER RAIL DIN 35; SIDE-ENTRY; CAGE CLAMP®CONNECTION; HORIZONTAL TYPE



Packing unit 50 pieces

Cross section from [mm ²]	0,2 mm ²
Cross section to [mm ²]	16 mm ²
Cross section from [AWG]	24 AWG
Cross section to [AWG]	06 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current CSA	90 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	76 A
Weight	27,594 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Current UL	65 A
Height	45,5 mm
Height	1,79 in
Width	12 mm
Width	0,472 in
Depth	58 mm
Depth	2,28 in
Strip length from	16 mm
Strip length to	17 mm
Strip length	0,65 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
283-101	BBJ	B/12/700/03	800	76	6,0
283-101	BV	07436/Co	800	76	6,0
283-101	CCA	NL3714	800	76	6,0
283-101	CSA	154112-1536072	600	90	24-6
283-101	CSM	017956	800	76	6,0
283-101	DEMKO	79928	750		16
283-101	Dep.MaE	CS4868N	600	80	16
283-101	DNV	E6999	800	76	6,0
283-101	GL	17295-00HH	800	76	16
283-101	KEMA	98.2759.06	800		16
283-101	KR	HMB05880-EL001	800	85	16

283-101	LCIE	218194	750		16
283-101	LR	91/20112(E1)	800	76	6,0
283-101	NEMKO	M52729/01	750		16
283-101	PRS	TE/1219/880590/98	800	76	6,0
283-101	RMR	99.00007.250	800	76	6,0
283-101	RosTesT	B09523	800	76	6,0
283-101	SABS	ED751/8191	750		16
283-101	SABS-EX	?e?741/85712/W491	550	76	
283-101	UL	E45172	600	65	24-6

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected