


NIMH RECHARGEABLE CYLINDRICAL BATTERY



SPECIFICATIONS

Model	:	MH1100AA4BP
Description	:	NiMH rechargeable battery, 'AA' size, flat cap
Nominal Capacity	:	1100 mAh at 220mA rate discharge (3 cycles allowed)
Nominal Voltage	:	4.8 Volt (After charge)
Cut-Off Voltage	:	4.0 Volt
End of Charge Voltage	:	<= 6.4 Volt
Approx. Weight	:	90 gram
Life Duration	:	>= 500 cycles (Comply to IEC 61951-2 Ed. 4.0:2017)
Charge	:	Trickle - 33-55 mA Recommend/Standard - 110 mA x 14-16 hours Quick - 1100 mA x 1.2 hours (with cut-off control)
Recharge	:	Every 3-6 months recommended
Temperature Environment	:	Standard charge - 0 degC to 45 degC Quick charge - 10 degC to 40 degC Discharge - -20 degC to 60 degC Storage - -20 degC to 40 degC
Trickle Charge	:	33mA for 28 days, no leakage, no explosion
Charge Retention	:	>60% for 28 days storage after standard charge
Leakage	:	No leakage, No explosion under standard operating condition
Vibration Test (for cell)	:	Battery remain normal after vibration at Amp: 4mm; Freq.: 1000/min for 60 min.
Shock Test (for cell)	:	Battery remain normal after dropping from 450mm to an Oak board for 3 times


Typical Standard Charge Characteristics (Cylindrical Cell)




Typical Quick Charge Characteristics (Cylindrical Cell)



Typical Discharge Characteristics (Cylindrical Cell)



Typical Charge Retention Characteristics (Cylindrical Cell)



Information is for references only. Performance varies with time, usage and storage condition. 1 year limited guarantee against manufacturing defects. Other problem caused by misuse, mishandling of cell, or malfunction of equipment, is not under the warranty.


Model : MH1100AA4BP
Version : 2.60

WELL LINK
INDUSTRIAL LIMITED

K306R99


NIMH RECHARGEABLE CYLINDRICAL BATTERY

DRAWING



5	Shrink Tube	2
4	Soldering Tags	2
3	Connecting Tags	3
2	Green PVC Shrink	1
1	NiMH AA 1100mAh Battery	4
Item	Details	Qty

Printing



KINETIC[®]

MH1100AA4BP

NiMH 4.8V 1100mAh
Standard charge : 110mA x 16h

Must be recycled
or disposed of
properly.
HR15/51



Information is for references only. Performance varies with time, usage and storage condition. 1 year limited guarantee against manufacturing defects. Other problem caused by misuse, mishandling of cell, or malfunction of equipment, is not under the warranty.

Model : MH1100AA4BP
Version : 2.60

WELL LINK
INDUSTRIAL LIMITED

K306R99