



| Symbol | Switching temp. [°C] |
|-----------------|-------------------------|
| AM03-90 | 90 |
| AM03-95 | 95 |
| AM03-100 | 100 |
| AM03-105 | 105 |
| AM03-110 | 110 |
| AM03-115 | 115 |
| AM03-120 | 120 |
| AM03-150 | 150 |
| AM04-90 | 90 |
| AM04-95 | 95 |
| AM04-100 | 100 |
| AM04-105 | 105 |
| AM04-110 | 110 |
| AM04-115 | 115 |
| AM04-120 | 120 |
| AM04-150 | 120 |
| AB03-90 | 90 |
| AB03-95 | 95 |
| AB03-100 | 100 |
| AB03-105 | 105 |
| AB03-110 | 110 |
| AB03-115 | 115 |
| AB03-120 | 120 |
| AB03-125 | 125 |
| AB03-130 | 130 |
| AB03-150 | 150 |

Bimetallic thermostats (temperature dependant switches) with single contact NC, with 60 mm long leads. The AM04 thermostats are fitted with holder 24 x 10 mm, with hole 4,3 mm, that enables direct fixation on a heatsink or equipment housing .

| | |
|---------------------------------|---|
| Rated current (max) | : AM03 - 2,5 A (3,6 A/2000 operations) |
| | : AB03 - 6,3 A (10 A/2000 operations) |
| Maximal voltage | : 250 V AC, 50-60 Hz |
| Output contacts | : NC |
| Switching temperature tolerance | : $\pm 5^{\circ}\text{C}$ |
| Hysteresis | : $30^{\circ}\text{C} \pm 15^{\circ}\text{C}$ |
| Reaction time | : max 50 s |
| No. of operation at rated load | : 10000 |
| Dimensions | : AM03 - 8,6 x 18 x 4,5 (L x H x W) |
| | : AB03 - 14,5 x 5,5 (dia. x H) |
| Leads length | : 60 mm |