

ISS		ZONE		REVISIONS		DESCRIPTION\PER REQUEST\DATE						
1	2	3	4	5	6	7	8					
<p>FLARE TO $\phi 8.3 \pm 0.07$</p> <p>FORMING</p> <p>STAMP (IF ANY)</p> <p>22.6 REF.</p> <p>$\phi 2.7$</p> <p>$\phi 3.8$</p>												
<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER Q0-B-626</p> <p>2. BRASS PER Q0-B-613</p> <p>3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE</p> <p>5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>6. JIS H 3260, C 3501</p>												
<p>RECOMMENDED CABLE STRIPPING DIM'S</p>												
<p>1. CRIMPED FERRULE HEX CRIMP SIZE .178"</p> <p>2. CRIMPED CONTACT PIN HEX CRIMP SIZE .068"</p>												
10	FERRULE	NOTE 6	NOTE 3	1	FR-52/44-38/3X14							
9	SLEEVE	DELTRIN	NATURAL	1	SL-25/17X129							
8	CONTACT PIN	NOTE 1	NOTE 5	1	B3000-8-25/D6							
7	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08							
6	SPRING	SK5	NOTE 4	1	B50000-6							
5	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5							
4	GASKET	RUBBER	RED	1	GS-115/BX15							
3	INSULATOR	DELTRIN	NATURAL	1	B50002-3-50							
2	BODY	NOTE 1	NOTE 3	1	B50002-2-38/27							
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B							
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A	FILE NO.		
						DIMENSIONS ARE IN MILLIMETERS			PART NO. B1121E1-ND3G-5-50		<h1 style="text-align: center;">Amphenol</h1> <p style="text-align: center;">TITLE BNC CRIMP PLUG (FOR RG-174/U,188A/U,316/U)</p> <p style="text-align: center;">DRAWING NO. KJ-B1121E1-ND3G-316U-50</p> <p style="text-align: center;">ITEM NO.</p>	
						UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED DATE 10-11-01'			
						0.5-6 = ± 0.2			CHECKED DATE 10-11-01'			
						6-30 = ± 0.4			DRAWN DATE 10-11-01'			
						30-120 = ± 0.6						
						120-315 = ± 1						
						315-1000 = ± 1.6						
						1000-2000 = ± 2.4						

Amphenol

TITLE BNC CRIMP PLUG
(FOR RG-174/U,188A/U,316/U)

DRAWING NO. KJ-B1121E1-ND3G-316U-50

ITEM NO.