



NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
14	NUT		NOTE 1	NOTE 3	1 B5291-14
13	HEX NUT		NOTE 1	NOTE 3	1 B5205-12-95/54
12	WASHER		NOTE 2	NOTE 3	1 WS-85/65X05
11	GASKET	SILICONE	RED		1 GS-8/5.3X5
10	TOP HAT		NOTE 1	NOTE 5	1 B1141E1-11-37/32
9	WASHER		NOTE 2	NOTE 3	1 WS-128/9X08
8	SPRING		SK5	NOTE 4	2 B50000-6
7	RETAINER RING		NOTE 1	NOTE 3	1 B50000-5
6	GASKET	RUBBER	RED		1 GS-115/8X15
5	CONTACT PIN		NOTE 1	NOTE 6	1 B5091-6-50
4	INSULATOR	DELTRIN	NATURAL		1 B50002-3-50
3	BODY		NOTE 1	NOTE 3	1 B5291-3-11/32
2	HOUSING		NOTE 1	NOTE 3	1 B5091-2
1	SHELL		NOTE 1	NOTE 3	1 B50000-1-B

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
 5. SILVER PL. 80 MIN. THICK OVER COPPER STRIKE
 6. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

DIMENSIONS ARE IN MILLIMETERS		PART NO.	B1142E1-ND3G-1-50
UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVED	DATE
0.5-6 = ±0.2			10-11-01'
6-30 = ±0.4		CHECKED	DATE
30-120 = ±0.6			10-11-01'
120-315 = ±1		DRAWN	DATE
315-1000 = ±1.6			10-11-01'
1000-2000 = ±2.4		FILE NO.	

1. CONTACT PIN TO SOLDER

Amphenol

TITLE BNC R/A CLAMP PLUG
(FOR RG-58C/U,58/U,142A/U)

DRAWING NO. KJ-B1142E1-ND3G-58U-50

ITEM NO.