



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- BRASS PER QQ-B-613
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- PHOSPHOR BRONZE PER QQ-B-750
- GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES

0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

| | |
|----------|---------------------|
| PART NO. | B6251C1-003-NT3G-50 |
| APPROVED | DATE 10-11-01' |
| CHECKED | DATE 10-11-01' |
| DRAWN | DATE 10-11-01' |

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO |
|-----|-------------|----------|---------|------|----------------|
| 4 | LOCK RING | NOTE 2 | NOTE 3 | 1 | B7700-4 |
| 3 | CONTACT PIN | NOTE 4 | NOTE 5 | 1 | 112515-3 |
| 2 | INSULATOR | NOTE 6 | NATURAL | 1 | 112515-2 |
| 1 | BODY | NOTE 1 | NOTE 3 | 1 | 222006-175-1-B |

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO |
|-----|-------------|----------|---------|------|----------------|
| 4 | LOCK RING | NOTE 2 | NOTE 3 | 1 | B7700-4 |
| 3 | CONTACT PIN | NOTE 4 | NOTE 5 | 1 | 112515-3 |
| 2 | INSULATOR | NOTE 6 | NATURAL | 1 | 112515-2 |
| 1 | BODY | NOTE 1 | NOTE 3 | 1 | 222006-175-1-B |

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO |
|-----|-------------|----------|---------|------|----------------|
| 4 | LOCK RING | NOTE 2 | NOTE 3 | 1 | B7700-4 |
| 3 | CONTACT PIN | NOTE 4 | NOTE 5 | 1 | 112515-3 |
| 2 | INSULATOR | NOTE 6 | NATURAL | 1 | 112515-2 |
| 1 | BODY | NOTE 1 | NOTE 3 | 1 | 222006-175-1-B |

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO |
|-----|-------------|----------|---------|------|----------------|
| 4 | LOCK RING | NOTE 2 | NOTE 3 | 1 | B7700-4 |
| 3 | CONTACT PIN | NOTE 4 | NOTE 5 | 1 | 112515-3 |
| 2 | INSULATOR | NOTE 6 | NATURAL | 1 | 112515-2 |
| 1 | BODY | NOTE 1 | NOTE 3 | 1 | 222006-175-1-B |

| | |
|---------|--|
| FILE NO | |
|---------|--|