

M 2381



Euromas
Enclosure, polycarbonate
Order no.: 02238200

Colour of enclosure group

Light grey, similar to RAL 7035; special colours on request

Protection class

Depending on the model: IP 65 or IP 66/DIN EN 60529; IP 67 available on request for some sizes.


Enclosure material

ABS, PC (UV stabilised) and selected sizes in PC UL 94 V0 (additional UL 94 V0 versions on request), seal made of CR; for details see Technical Information

Scope of delivery: Lid and base, lid screws made of V2A, self-tapping screws for mounting bosses

Note: G = Design with crystal-clear lid.

IP = Ingress protection acc. to DIN EN 60529



| | |
|-----------|----------|
| A | 160 mm |
| B | 120 mm |
| C | 75 mm |
| a1 | 153 mm |
| a2 | 134,2 mm |
| b1 | 113 mm |
| b2 | 74,2 mm |
| c1 | 15 mm |
| c2 | 68,5 mm |

Technical drawings

3D product data in STEP format:

[Registration necessary](#)

Catalogue drawing in DXF format:

[02238200_M-2381.dxf](#) (673 KB)

Basic drawing for processing work:

[02238200_M-2381-G.dxf](#) (362 KB)

Catalogue drawing in PDF format:

[02238200_M-2381.pdf](#) (90 KB)

Chapter download

[Euromas_ABS_PC_GB.pdf](#) (338 KB)

Accessories



Mounting plates, laminated paper (Pertinax), galvanised steel for version 260

22001100 [M](#) For EM/ET 238, M/T 238, M/T 246



Knurled screws

22003200 [RD](#) For M/T 240-2401



Rubber feet, plug-in

22003300 [E](#) For M/T 208-260



Silicone seal for lid

22004300 [SIL](#) For M/T 238, M/T 246



Wall brackets on rear, screw-on, polycarbonate

22004900 [WL](#) For M/T 210-243, M/T 246-253



DIN rails DIN EN 60715 TH 15

22002000 [TS 15](#) For M/T 219-220, M/T 231-235, M/T 238, M/T 246, P 325, M/T 2381



DIN rails DIN EN 60715 G 32

22002010 [TS 32](#) For M/T 219-220, M/T 231-235, M/T 238, M/T 246, P 316, P 325, M/T 2381



DIN rails DIN EN 60715 TH 35

22002020 [TS 35](#)

For M/T 219-220, M/T 231-235, M/T 238, M/T 246, P 316, P 325, M/T 2381



Threaded inserts for mounting bosses

59002810 [DODGE](#)

ND = 4.0 x 6.5

[M3x6,5](#)

59002820 [DODGE](#)

ND = 5.4 x 9.5

[M4x9,5](#)

* = Available on request