

## 2.1 TYPES – TECHNICAL DATA



Type	Order No.	Nominal voltage (V)	Typical capacity <sup>1)</sup> (mAh)	Standard load (k $\Omega$ )	Max. discharge current (continuous) (mA)	Max. discharge current (pulse) (mA)	Weight (g)
CR 1/3 N	6131 101 501	3	170	5.6	20	80	3.0
2 CR 1/3 N (p28 pxl)	6231 210 501	6	170	13	20	80	8.8
CR 1216	6216 101 501	3	27	39	2	5	0.7
CR 1220	6220 101 501	3	35	39	2	5	0.8
CR 1616	6616 101 501	3	55	39	3	8	1.2
CR 1620	6620 101 501	3	70	20	3	8	1.2
CR 2016	6016 101 501	3	90	15	3	10	1.8
CR 2025	6025 101 501	3	165	10	3	10	2.5
CR 2032	6032 101 501	3	230	5.6	3	10	3.0
CR 2430	6430 101 501	3	280	5.6	3	20	4.0
CR 2450	6450 101 501	3	560	5.6	2	20	6.2

**TAB. 3**

Technical data, CR Primary Lithium Button Cells

<sup>1)</sup> Nominal capacity is determined to an end voltage of 2.0 V (type 2 CR 1/3 N: 4.0 V) when the battery is allowed to discharge at standard load level at 20°C