

DSP60-5



Sales Region	Worldwide (except Japan)
Series	DSP
Model	
Status	Production
Feature	DIN rail installation compatible
Options	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	120 to 370Vdc
Efficiency	80% Typ.
Rated Output Voltage[DC]	5Vdc
Output Voltage Range[DC]	5 to 5.5Vdc
Maximum Output Current	7A
Maximum Output Power	35W

Package Type & Size

Package / Mounting	DIN rail
Width(W)	71mm Nom. (2.80in Nom.)
Height(H)	91mm Nom. (3.58in Nom.)
Depth(D)	55.6mm Nom. (2.19in Nom.)
Weight	250g Typ. (0.6lbs Typ.)

Other

Operating Temp. Range	-25 to 71°C
Cooling	Convection
Safety Standard(Certified)	EN60950-1
	UL60950-1
	UL508
Safety Standard(Conformed)	UL1310 Class 2

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products

! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.