



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. BRIGHT TIN PL. 200 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 100 MIN. THICK
 5. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS									
UNLESS OTHERWISE SPECIFIED TOLERANCES									
0.5-6 = ±0.2									
6-30 = ±0.4									
30-120 = ±0.6									
120-315 = ±1									
315-1000 = ±1.6									
1000-2000 = ±2.4									

PART NO.		F6551A1-002-NTT	
APPROVED	DATE	10-11-01'	
CHECKED	DATE	10-11-01'	
DRAWN	DATE	10-11-01'	

Amphenol	
TITLE	F PANEL JACK
DRAWING NO.	KJ-F6551A1-002-NTT
ITEM NO.	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
-----	-------------	----------	--------	------	-------------

6	LOCK RING	NOTE 1	NOTE 3	1	F6551A1-001-6
5	GASKET	SILICONE	RED	1	GS-111/75XD18
4	INSULATOR	NOTE 5	NATURAL	1	1017669-4
3	CONTACT PIN	NOTE 2	NOTE 4	1	F6551A1-002-3
2	INSULATOR	NOTE 5	NATURAL	1	F6551A1-002-2
1	BODY	NOTE 1	NOTE 3	1	F6551A1-001-1

SCALE	4/1	ISSUE	A
-------	-----	-------	---

FILE NO.	
----------	--