

Attachable heatsinks

- universal clip on heatsinks for type TO 218, TO 229, TO 247, TO 248, SIP-Muliwatt and similar
- easy assembly by pushing the heatsink onto the component
- for vertical and horizontal fastening by soldering
- fin height variations on request
- special design accord. to customized specification

| | | | | | |
|----------------------------|--|-----------------|--|--|--|
| art. no. | | 20,2 K/W | | | |
| FK 245 MI 247 O | without soldering lug | | | | |
| art. no. | | 20,5 K/W | | | |
| FK 245 MI 247 H | with soldering lug for horizontal mounting | | | | |
| art. no. | | 19,7 K/W | | | |
| FK 245 MI 247 V | with soldering lug for vertical mounting | | | | |
| art. no. | | 18,4 K/W | | | |
| FK 243 MI 247 O | without soldering lug | | | | |
| art. no. | | 19 K/W | | | |
| FK 243 MI 247 H | with soldering lug for horizontal mounting | | | | |
| art. no. | | 18,4 K/W | | | |
| FK 243 MI 247 V | with soldering lug for vertical mounting | | | | |
| material: | copper (Cu) | | | | |
| surface: | solderable surface | | | | |
| material thickness: | 0.6 mm | | | | |

Heatsinks for D PAK
Heatsinks for transistors
Kapton insulator washers
Vibration dampers

→ C 21
→ C 4 – 9
→ E 14
→ E 39

Vibration dampers
U-shaped heatsink
Aluminium oxide wafers
Technical introduction

→ E 39
→ A 121 – 122
→ E 15 – 16
→ A 2 – 7

C 12

A

B

C

D

E

F

G

H

I

K

L

M

N