


HWS300-24



<b>Sales Region</b>	Worldwide
<b>Series</b>	HWS
<b>Model</b>	HWS300
<b>Status</b>	 Production
<b>Feature</b>	
<b>Options</b>	
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Voltage Range[DC]	120 to 330Vdc
Efficiency	85% Typ.
Rated Output Voltage[DC]	24Vdc
Output Voltage Range[DC]	19.2 to 28.8Vdc
Maximum Output Current	14A
Maximum Average Current	
Maximum Peak Current	16.5A
Maximum Output Power	336W
Maximum Average Power	
Maximum Peak Power	

### Package Type & Size

Package / Mounting	Enclosed / Unit type
Width(W)	61mm Nom. (2.40in Nom.)
Height(H)	82mm Nom. (3.23in Nom.)
Depth(D)	165mm Nom. (6.50in Nom.)
Weight	1000g Typ. (2.2lbs Typ.)

### Other

Operating Temp. Range	-10 to 70°C
Cooling	Forced air

Safety Standard(Certified)	CSA60950-1 EN60950-1 UL60950-1 CSA62368-1 EN62368-1 UL62368-1 CSA C22.2 No.14-M95 UL508 EN50178
Safety Standard(Conformed)	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
 ! This PDF document was created based on the data listed on the TDK Corporation website.  
 ! All specifications are subject to change without notice.