


# POWER RELAY

## 1 POLE - 5A Medium Load Control

### JV Series

#### ■ FEATURES

- UL, CSA, VDE, CQC recognized
  - Low profile and space saving
    - Height: 12.5 mm
    - Mounting space: 175 mm $\bar{r}$
  - High sensitivity in small package
    - Operating power: 0.113 to 0.13 W
    - Nominal power: 0.2 to 0.3 W
  - High insulation with reinforced insulation system (between coil and contacts)
    - Insulation distance: 8 mm
    - Dielectric strength: 5,000 VAC
    - Surge strength: 10,000 V
  - Plastic materials
    - UL94 flame class V-0
    - UL CTI level class 2
  - Plastic sealed type, RTIII
  - RoHS compliant.
- Please see page 7 for more information



#### ■ PARTNUMBER INFORMATION

[Example]       $\frac{JV}{(a)}$  -  $\frac{12}{(*) (b)}$     $\frac{S}{(c)}$  -  $\frac{K}{(d)}$     $\frac{T}{(e)}$

(a)	Relay type	JV	: JV-Series
(b)	Coil rated voltage	12	: 3.....48 VDC Coil rating table at page 3
(c)	Coil type	Nil S	: Standard type (300mW) : High sensitive type (200mW)
(d)	Enclosure	K	: Plastic sealed type, RTIII
(f)	Construction	T	: Insertion error preventing structure

Note: Actual marking omits the hyphen (-) of (\*)

## ■ SPECIFICATION

Item			Standard type	High sensitive type
			JV - ( )	JV - ( ) S
Contact Data	Configuration		1 form A (SPST-NO)	
	Construction		Single	
	Material		Silver alloy	
	Resistance (Initial)		Max. 70 mΩ at 6 VDC, 1 A	
	Contact rating		5A, 250VAC / 30VDC (resistive load)	
	Max. carrying current		5A	
	Max. switching voltage		250VAC / 150 VDC	
	Max. switching power		1,250VA / 150W	
	Max. switching current		5A	
	Min. switching load *		100 mA, 5 VDC	
Life	Mechanical		Min. 5 x 10 <sup>6</sup> operations	
	Electrical		Min. 100 x 10 <sup>3</sup> operations	
Coil Data	Rated power (at 20 °C)		300mW	200mW
	Operate power (at 20 °C)		130mW	113mW
	Operating temperature range		-40 °C to +70 °C (no frost)	
Timing Data	Operate (at nominal voltage)		Max. 8 ms (without bounce)	
	Release (at nominal voltage)		Max. 4 ms (no diode)	
Insulation	Resistance (initial)		Min 1,000MΩ at 500VDC	
	Dielectric strength	Open contacts	750VAC, 1 min.	
		Contacts to coil	5,000VAC, 1 min.	
	Surge strength	Coil to contacts	10,000V / 1.2 x 50μs standard wave	
Other	Vibration resistance	Misoperation	10 to 55 to 10Hz single amplitude 0.825 mm	
		Endurance	10 to 55Hz double amplitude 2.5 mm	
	Shock	Misoperation	Min. 100m/s <sup>2</sup> (11 ± 1ms)	
		Endurance	Min. 1,000m/s <sup>2</sup> (6 ± 1ms)	
	Weight	Approximately 4.3 g		
	Sealing	Plastic sealed RTIII		

\* Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

## ■ COIL RATING

Standard type (300 mW)

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance +/- 10% (Ohm)	Must Operate Voltage (VDC) *	Must Release Voltage (VDC) *	Rated Power (mW)
3	3	30	1.98	0.15	300 mW
5	5	83.3	3.3	0.25	
6	6	120	3.96	0.3	
9	9	270	5.94	0.45	
12	12	480	7.9	0.6	
18	18	1,080	11.9	0.9	
24	24	1,920	15.8	1.2	
48	48	7,680	31.7	2.4	

High sensitive type (200 mW)

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance +/- 10% (Ohm)	Must Operate Voltage (VDC) *	Must Release Voltage (VDC) *	Rated Power (mW)
3	3	45	2.25	0.15	200 mW
5	5	125	3.75	0.25	
6	6	180	4.5	0.3	
9	9	405	6.75	0.45	
12	12	720	9	0.6	
18	18	1,620	13.5	0.9	
24	24	2,880	18	1.2	

Note: All values in the tables are valid for 20°C and zero contact current.

\* Specified operate values are valid for pulse wave voltage.








■ Please use at rated coil voltage. Please refer to characteristic data and set up adequate voltage in case of use at over voltage.

## ■ SAFETY STANDARDS


Type	Compliance	Contact rating
UL	UL 508, UL 873	Flammability: UL 94-V0 (plastics)
	E56140	5A, 250 VAC / 30 VDC (resistive) 1/8 HP, 125VAC/250VAC Pilot duty: C300
CSA	C22.2 No. 14 LR 35579	
VDE	IEC/EN61810-1 EN60335-1 clause 15.3; 16.3; 29.1; 29.2; 29.3 EN60730-1 clause 12.2; 13.2; 20.1; 20.2; 20.3	5A, 250VAC (cosφ=1)
CQC	GB/T21711.1 GB15092 170002164384	5A 250VAC (JV-( )S-KT)

## CHARACTERISTIC DATA


(Characteristic data is not guaranteed value but measured values of samples from production line.)




Distribution of operate/release voltage




Distribution of operate/release time




Distribution of contact resistance




Mechanical life test



Electrical life test




Electrical life test




## ■ DIMENSIONS


### ● Dimensions



### ● Schematics (BOTTOM VIEW)



### ● PC board mounting hole layout (BOTTOM VIEW)



- \* Dimensions of the terminals do not include thickness of pre-solder.
- \* Dimensions do not include tolerances.
- \* Tolerance of PC board mounting hole layout :  $\pm 0.1$  unless otherwise specified.

Unit: mm  
( ): Reference

## Cautions

- All values mentioned in this datasheet are provided under ideal conditions. Please perform the confirmation test before actual use.
- Reflow soldering is prohibited.
- Do not use relays in the atmosphere with sulfide gas, chloride gas or nitric oxide. Contact resistance may increase.
- Do not use silicon or silicon-containing product or materials near relays. It may cause contact failure.

## RoHS Compliance and Lead Free Information

### 1. General Information

- All signal and power relays produced by Fujitsu Components are compliant with RoHS directive 2002/95EC including amendments.
- Cadmium as used in electrical contacts is exempted from the RoHS directives on October 21st, 2005. (Amendment to Directive 2002/95/EC)
- All of our signal and power relays are lead-free. Please refer to Lead-Free Status Info for older date codes at: <http://www.fujitsu.com/us/downloads/MICRO/fcai/relays/lead-free-letter.pdf>
- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.

### 2. Recommended Lead Free Solder Profile

- **Recommended solder Sn-3.0Ag-0.5Cu.**

#### **Flow Solder condition:**

Pre-heating: maximum 120°C within 90 sec.  
Soldering: dip within 5 sec. at 255°C±5°C solder bath  
Relay must be cooled by air immediately after soldering

#### **Solder by Soldering Iron:**

Soldering Iron: 30-60W  
Temperature: maximum 340-360°C  
Duration: maximum 3 sec.

**We highly recommend that you confirm your actual solder conditions**

### 3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

### 4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

## Fujitsu Components International Headquarter Offices

<p><b>Japan</b>  FUJITSU COMPONENT LIMITED  Shinagawa Seaside Park Tower 19F,  12-4, Higashi-shinagawa 4-chome, Shinagawa-ku,  Tokyo, 140-0002, Japan  Tel: (81-3) 3450-1682  Fax: (81-3) 3474-2385  Email: fcl-contact@cs.jp.fujitsu.com  Web: www.fujitsu.com/jp/fcl/</p>	<p><b>Asia Pacific</b>  FUJITSU COMPONENTS ASIA, LTD.  102E Pasir Panjang Road  #01-01 Citilink Warehouse Complex  Singapore 118529  Tel: (65) 6375-8560  Fax: (65) 6273-3021  Email: fcal@sg.fujitsu.com  Web: www.fujitsu.com/sg/products/devices/components</p>	<p><b>Korea</b>  FUJITSU COMPONENTS KOREA LIMITED  Alpha Tower #403, 645 Sampyeong-dong,  Bundang-gu, Seongnam-si, Gyeonggi-do,  13524 Korea  Tel: (82) 31-708-7108  Fax: (82) 31-709-7108  Email: fcal@sg.fujitsu.com  www.fujitsu.com/sg/products/devices/components/</p>
<p><b>North and South America</b>  FUJITSU COMPONENTS AMERICA, INC  2290 North First Street, Suite 212  San Jose, CA 95131, USA  Tel: (1-408) 745-4900  Fax: (1-408) 745-4970  Email: components@us.fujitsu.com  Web: us.fujitsu.com/components</p>	<p><b>China</b>  FUJITSU ELECTRONIC COMPONENTS (SHANGHAI) CO., LTD.  Unit 4306, InterContinental Center  100 Yu Tong Road, Shanghai 200070,  China  Tel: (86-21) 3253 0998  Fax: (86-21) 3253 0997  Email: fcsh@cn.fujitsu.com  Web: www.fujitsu.com/cn/products/devices/components/</p>	
<p><b>Europe</b>  FUJITSU COMPONENTS EUROPE B.V.  Diamantlaan 25  2132 WV Hoofddorp  Netherlands  Tel: (31-23) 5560910  Fax: (31-23) 5560950  Email: info@fceu.fujitsu.com  Web: www.fujitsu.com/uk/components</p>	<p><b>Hong Kong</b>  FUJITSU COMPONENTS HONG KONG CO., LTD  Unit 506, Inter-Continental Plaza  No.94 Granville Road, Tsim Sha Tsui, Kowloon,  Hong Kong  Tel: (852) 2881-8495  Tex: (852) 2894-9512  Email: fcal@sg.fujitsu.com  Web: www.fujitsu.com/sg/products/devices/components/</p>	

© 2019 Fujitsu Components Europe B.V. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

The contents, data and information in this datasheet are provided by Fujitsu Component Ltd. as a service only to its user and only for general information purposes. The use of the contents, data and information provided in this datasheet is at the users' own risk.

Fujitsu has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

Fujitsu Components Europe B.V. and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof.

Nor do Fujitsu Components Europe B.V. and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. July 5th, 2019