


Ring Terminals

Electrolytic Copper
Tin Plated
Easy Entry
P.V.C. Insulation



Part No	ϕd_2	B	L	F	H	ϕD	Wire Size AWG(mm ²)	Current Rating	Insulation Color	Qty/Box	Weight/Box
KTL-001-01	3.2	5.5	16.5	4.3						3000	1.2 kg
KTL-001-02	4.3	8.0	20.0	6.6	9.5	3.5	22-20 (0.25-1.0)	10 A	Red	3000	1.6 kg
KTL-001-03	5.3	8.0	20.0	6.6						3000	1.6 kg
KTL-001-04	3.2	5.5	18.0	4.3						3000	1.8 kg
KTL-001-05	3.7	5.5	18.0	4.3						3000	1.7 kg
KTL-001-06	3.2	6.6	20.9	6.6						3000	2.0 kg
KTL-001-07	3.7	6.6	20.9	6.6						3000	2.1 kg
KTL-001-08	4.3	8.0	22.3	7.3	11.0	4.0	22-16 (0.25-1.65)	19 A	Red	3000	2.3 kg
KTL-001-09	4.3	6.6	20.9	6.6						3000	2.0 kg
KTL-001-10	5.3	8.0	22.3	7.3						3000	2.2 kg
KTL-001-11	6.4	11.6	28.2	11.4						2000	2.3 kg
KTL-001-12	8.4	11.6	28.2	11.4						2000	1.9 kg
KTL-001-13	3.2	8.5	23.0	7.75						2000	2.0 kg
KTL-001-14	3.7	6.6	20.6	6.3						2000	1.9 kg
KTL-001-15	4.3	8.5	23.0	7.75						2000	2.0 kg
KTL-001-16	4.3	6.6	20.6	6.3	11.0	4.5	16-14 (1.04-2.63)	27 A	Blue	2000	1.6 kg
KTL-001-17	5.3	9.5	23.0	7.25						2000	2.0 kg
KTL-001-18	6.4	12.0	28.0	11.0						2000	2.7 kg
KTL-001-19	8.4	12.0	28.0	11.0						2000	2.6 kg
KTL-001-20	10.5	13.6	31.7	13.9						1500	1.8 kg
KTL-001-21	4.3	9.5	26.9	8.2						1500	2.0 kg
KTL-001-22	5.3	9.5	26.9	8.2	13.7	6.3	12-10 (2.63-4.6)	37 A	Yellow	1500	2.2 kg
KTL-001-23	6.4	12.0	28.3	8.5						1500	2.5 kg
KTL-001-24	3.7	9.5	26.7	8.25						1500	3.1 kg
KTL-001-25	4.3	9.5	26.7	8.25						1500	2.9 kg
KTL-001-26	5.3	9.5	26.7	8.25						1500	2.8 kg
KTL-001-27	6.4	12.0	32.7	13.0	13.7	6.3	12-10 (2.63-6.64)	48 A	Yellow	1500	2.5 kg
KTL-001-28	8.4	15.0	34.9	13.7						1500	4.0 kg
KTL-001-29	10.5	15.0	34.9	13.7						1500	3.7 kg

Unit = mm