



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. BERYLLIUM COPPER PER QQ-C-530
5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	FERRULE	COPPER	NOTE 3	1	FR-38/3X7C
5	COVER	NOTE 2	NOTE 3	1	CV-29X05-T
4	RETAINER RING	NOTE 4	NOTE 3	1	MMCX1112A1-5-C
3	CONTACT PIN	NOTE 1	NOTE 5	1	MMCX1112A1-4-B
2	INSULATOR	NOTE 6	NATURAL	1	MMCX1112A1-3T-50-B
1	HOUSING WITH BODY	NOTE 1	NOTE 3	1	MMCX1112A1-1S-23/17-B

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

PART NO.	
MMCX1112A1-3GT30G-5-50	
APPROVED	DATE
	10-11-01'
CHECKED	DATE
	10-11-01'
DRAWN	DATE
	10-11-01'
FILE NO.	

Amphenol	
TITLE MMCX R/A CRIMP PLUG (FOR RG-174/U,188A/U,316/U)	
DRAWING NO. KJ-MMCX1112A1-3GT30G-316U-50	
ITEM NO.	

1 2 3 4 5 6 7 8