





MORSETTI PER C.S. CARRELLO

BLOCS DE JONCTION C.I. ÉTRIER REMONTANT

PRINTKLEMMEN LIFTPRINZIP

Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale Tension nominale	Tensione nominale Bemessungsspannung	V
Rated Current Intensità nominale	Corrente nominale Bemessungsstrom	A
Types of cables Type du conducteur	Tipo cavi Leitungstypen	
Nominal cross section Section nominale	Sezione nominale Nennquerschnitt	mm ² AWG
Stripping length Longueur de dénudage	Lunghezza spelatura Abisolierlänge	mm
Torque Couple de serrage	Coppia di torsione Drehmoment	Nm Lb-in
Temperature Température	Temperatura Temperatur	°C
Housing Corps isolant	Corpo isolante Isolierkörper	
Captive Screw Vis Imperdabile	Vite Imperdibile Unverlierbare Schraube	
		mm

	IMQ	EN60998
	VDE	EN60998
	cUL	UL1059 + C22.2 n°158

Poles Pôles	Poli Polzahl	X
Colours Couleurs	Colori Farben	Y
Other information Autres données	Altri dati Weitere Informationen	D-

How to order Référence de commande	Ordinazione Bestellschlüssel
MRT5 P5 / X	SQ Y N...
Type Pitch Poles	Version Colors Printing
Type Passo Poli	Versione Colori Numerazione
Type Pas Pôles	Version Couleurs Marquage
Type Rastermaß Polzahl	Version Farben Bedruckung





MRT5 MRT5..SQ*

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensteckbare Blöcke

Poles · Poli · Pôles · Polzahl



2/3



5 - 5,08		
320		
24		
		
0,2 ÷ 4 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12
6		
0,5	/	5
110		
PA - UL 94 V0		
M3		
 0,6 x 3,5		

V	A	mm ² /AWG
450	24	0,5 ÷ 2,5
450	24	0,5 ÷ 2,5
300	16	24 ÷ 12

min 2 - max...		
		
D/A1		







MRT5..DP

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensteckbare Blöcke

Poles · Poli · Pôles · Polzahl



2/3



5 - 5,08		
320		
24		
		
0,2 ÷ 4 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12
6		
0,5	/	5
110		
PA - UL 94 V0		
M3		
 0,6 x 3,5		

V	A	mm ² /AWG
450	24	0,5 ÷ 2,5
450	24	0,5 ÷ 2,5
300	16	24 ÷ 12

min 2 - max...		
		
D/A1		







MRT5 MRT5..SQ*

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensteckbare Blöcke


Poles · Poli · Pôles · Polzahl



2/3



7,5 - 7,62		
500		
24		
		
0,2 ÷ 4 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12
6		
0,5	/	5
110		
PA - UL 94 V0		
M3		
 0,6 x 3,5		

V	A	mm ² /AWG
750	24	0,5 ÷ 2,5
750	24	0,5 ÷ 2,5
300	16	24 ÷ 12

min 2 - max...		
		
D/A1		







MRT5..DP

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensteckbare Blöcke


Poles · Poli · Pôles · Polzahl


2/3



7,5 - 7,62		
500		
24		
		
0,2 ÷ 4 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12
6		
0,5	/	5
110		
PA - UL 94 V0		
M3		
 0,6 x 3,5		

V	A	mm ² /AWG
750	24	0,5 ÷ 2,5
750	24	0,5 ÷ 2,5
300	16	24 ÷ 12

min 2 - max...		
		
D/A1		







MRT5 MRT5..SQ*

Interlocking modules - Modulo componibile
Elements modulaires - Zusammensteckbare Blöcke

Poles · Poli · Pôles · Polzahl



1/2



10 - 10,16		
630		
24		
		
0,2 ÷ 4 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12	0,2 ÷ 2,5 30 ÷ 12
6		
0,5	/	5
110		
PA - UL 94 V0		
M3		
 0,6 x 3,5		

V	A	mm ² /AWG
750	24	0,5 ÷ 2,5
750	24	0,5 ÷ 2,5
300	16	24 ÷ 12

min 2 - max...		
		
D/A1		



* SQ Version = Horizontal version