



**SPECIFICATIONS**

**Electrical**  
 Current Rating: 2A AC, DC  
 Voltage Rating: 100V AC/ max.  
 Operating Temp.: -25°C ~ +85°C  
 Insulation Resistance: 1000MΩ/ min.  
 Dielectric Withstanding Voltage: 800V AC/ min.  
 Contact Resistance: 20mΩ/ max.

**Material**  
 Material: Nylon 66, UL94V-0

Poles	Dimension mm (in.)	
	A	B
2	2.0(0.079)	5.8(0.228)
3	4.0(0.157)	7.8(0.307)
4	6.0(0.236)	9.8(0.386)
5	8.0(0.315)	11.8(0.465)
6	10.0(0.394)	13.8(0.543)
7	12.0(0.472)	15.8(0.622)
8	14.0(0.551)	17.8(0.701)
9	16.0(0.630)	19.8(0.780)
10	18.0(0.709)	21.8(0.858)
11	20.0(0.787)	23.8(0.937)
12	22.0(0.886)	25.8(1.016)
13	24.0(0.945)	27.8(1.094)
14	26.0(1.024)	29.8(1.173)
15	28.0(1.102)	31.8(1.252)
16	30.0(1.181)	33.8(1.331)

**RoHS Compliant**

*Gold Star Connectors Co., Ltd.*

制表日: 2006/01/19      DRAWING. *Jolin*      APPROVED

UNIT		SCALE	PART NAME	
MM			HOUSING 2mm (CRIMP)	
APPD.	CKD.	TOLERANCE	PART NO.	REV.
			NCH200S-xx	A