



Insulator Material:PPS (UL 94V-0)  
 Contact Resistance:30m Ohm MAX at DC 100mA  
 Current Rating:1 AMP  
 Dielectric Withstanding Voltage:AC 500V For 1 minute  
 Temperature Rating:-55°C ~ +105°C  
 Insulator Resistance:1000M Ohm Min at DC 500V

NO OF CONTACT	A±0.15	B±0.15	C±0.15	D±0.15	E±0.15	F±0.15
20PPS	15.50	15.50	5.08	5.08	5.08	5.08
28PPS	18.04	18.04	7.62	7.62	7.62	7.62
32PPS	18.04	20.54	7.62	10.16	7.62	10.16
44PPS	23.48	23.48	12.70	12.70	12.70	12.70
52PPS	25.88	25.88	15.24	15.24	15.24	15.24
68PPS	31.04	31.04	20.32	20.32	20.32	20.32
84PPS	36.04	36.04	25.40	25.40	25.40	25.40

<p>RoHS Compliant</p>		<p><b>T&amp;T</b> Connection System Co., Ltd.</p>	
<p>APPD. 核准 HELEN</p>		<p>TOLERANCE 容許公差 0 ± .00 ± ANG ±</p>	<p>PART NAME 品名 THROUGH HOLE PLCC SOCKET</p>
<p>DWG. 製圖 ABBY</p>	<p>SCALE 比例 參考</p>	<p>UNIT 單位 M M</p>	<p>PART NO. 料號 PLCCTHBR-xxx</p>
<p>DATE 制表日 2014/05/09</p>	<p>PAGE 張數 1 OF 1</p>	<p>SIZE 紙張尺寸 A 4</p>	<p>REV. 版次 A</p>