

Standard extruded heatsinks

art. no. SK 59 ...		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 37.5 50 75 100 1000 mm ... \diamond (optional) TO 220</p>		
art. no. SK 122 ...		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 37.5 50 mm ... \diamond (optional) TO 3; CB</p>		
art. no. SK 107 ...		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 50 75 100 1000 mm</p>		
art. no. SK 181 ...		
<p>please indicate: ... $\left[\begin{array}{c} \\ \\ \end{array} \right]$ 50 75 100 1000 mm</p>		
art. no. SK 181 94 C 3 x TO 220 SK 181 94 C 3 x TO 220		
<p>retaining spring for transistor THF 409 TO 220 → A 115</p>		

Hole pattern
Profiles for PCB components
Heatsinks for PCB
Profiles for PCB mounting

→ A 21
→ A 91
→ A 89
→ A 89 - 112

Screw mounted guide rails
Thermal conductive material
Heatsink-cooling aggregates
Technical introduction

→ E 26 - 27
→ E 2 - 24
→ D 14
→ A 2 - 8

A 60