

Standard extruded heatsinks

|  |  |  |
|--|--|--|
| <p>art. no.</p> <p>SK 18 ...</p>   |  |  |
| <p>please indicate: ... <math>\left[ \begin{array}{c} \text{---} \\ \text{---} \end{array} \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3; CB</p> |  |  |
| <p>art. no.</p> <p>SK 63 ...</p>   |  |  |
| <p>please indicate: ... <math>\left[ \begin{array}{c} \text{---} \\ \text{---} \end{array} \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3; CB</p> |  |  |
| <p>art. no.</p> <p>SK 05 ...</p>   |  |  |
| <p>with slots for cover plates or PCBs</p>   |  |  |
| <p>please indicate: ... <math>\left[ \begin{array}{c} \text{---} \\ \text{---} \end{array} \right]</math> 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3; CB</p>      |  |  |
| <p>art. no.</p> <p>SK 402 ...</p>  |  |  |
| <p>please indicate: ... <math>\left[ \begin{array}{c} \text{---} \\ \text{---} \end{array} \right]</math> 100 mm ... <math>\diamond</math> (optional) TO 3; CB</p>                 |  |  |
| <p>art. no.</p> <p>SK 97 ...</p>   |  |  |
| <p>please indicate: ... <math>\left[ \begin{array}{c} \text{---} \\ \text{---} \end{array} \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3</p>     |  |  |

High decorative surfaces → A 9  
 Order example → A 21  
 Heatsink as visual & decor-parts → A 10  
 Drilling pattern for Solid State Relays → A 12

Heatsinks for Solid State Relay → A 11 – 12  
 Heatsink special design → A 135 – 136  
 Special profiles → A 138  
 Technical introduction → A 2 – 7