



Standard extruded heatsinks

<p>art. no.</p> <p><b>SK 581 ...</b></p>		
<p>please indicate: ... <math>\longleftrightarrow</math> 37.5 50 75 100 1000 mm</p>		
<p>art. no.</p> <p><b>SK 400 ...</b></p>		
<p>extruded heatsinks for PCB mounting → A 110</p>		
<p>please indicate: ... <math>\longleftrightarrow</math> 37.5 50 75 100 1000 mm</p>		
<p>art. no.</p> <p><b>SK 178 ...</b></p>		
<p>please indicate: ... <math>\longleftrightarrow</math> 37.5 75 100 1000 mm</p>		
<p>art. no.</p> <p><b>SK 134 ...</b></p>		
<p>please indicate: ... <math>\longleftrightarrow</math> 37.5 50 100 1000 mm</p>		
<p>art. no.</p> <p><b>SK 471 ...</b></p>		
<p>please indicate: ... <math>\longleftrightarrow</math> 37.5 50 75 1000 mm</p>		

High decorative surfaces → A 9  
 Order example → A 21  
 Heatsink as visual & decor-parts → A 10  
 Drilling pattern for Solid State Relays → A 12

Heatsinks for Solid State Relay → A 11 - 12  
 Heatsink special design → A 135 - 136  
 Special profiles → A 138  
 Technical introduction → A 2 - 7