

A


**Standard extruded heatsinks**

<b>art. no.</b>         <b>SK 45 ...</b>		
<b>please indicate:</b> ... <b>37.5 50 75 100 1000 mm</b> ... <b>(optional) TO 3; CB</b>		
<b>art. no.</b>         <b>SK 19 ...</b>		
<b>please indicate:</b> ... <b>37.5 50 75 100 1000 mm</b> ... <b>(optional) TO 3; CB</b>		
<b>art. no.</b>         <b>SK 28 ...</b>		
<b>please indicate:</b> ... <b>37.5 50 75 1000 mm</b> ... <b>(optional) TO 3; CB</b>		
<b>art. no.</b>         <b>SK 401 ...</b>		
<b>please indicate:</b> ... <b>100 1000 mm</b> ... <b>(optional) TO 3; CB</b>		
<b>art. no.</b>         <b>SK 72 ...</b>		
<b>please indicate:</b> ... <b>37.5 50 75 100 1000 mm</b> ... <b>(optional) TO 3; CB</b>		

N

**A 63**

High decorative surfaces → A 9  
 Order example → A 21  
 Heatsink as visual & decor-parts → A 10  
 Drilling pattern for Solid State Relays → A 12

Heatsinks for Solid State Relay → A 11 - 12  
 Heatsink special design → A 135 - 136  
 Special profiles → A 138  
 Technical introduction → A 2 - 7