



RECOMMENDED
CABLE STRIPPING DIM'S

1. CONTACT PIN TO SOLDER

- NOTES. FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. BERYLLIUM COPPER PER QQ-C-530
 5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468

11	HEX NUT	NOTE 1	NOTE 3	1	SMA1141C2-11-8/54
10	WASHER	NOTE 2	NOTE 3	1	WS-7/54X05
9	GASKET	SILICONE	RED	1	GS-7/5X24
8	TOP HAT	NOTE 1	NOTE 3	1	SMA1141C2-8-54/45
7	WASHER	NOTE 2	NOTE 3	1	WS-7/31X05
6	CONTACT PIN	NOTE 1	NOTE 5	1	SMA5200-6-143/105
5	INSULATOR	NOTE 6	NATURAL	1	SMA5200-5T-50
4	GASKET	SILICONE	RED	1	GS-6/43X06
3	RETAINER RING	NOTE 4	NATURAL	1	SMA5000-4-B
2	BODY	NOTE 1	NOTE 3	1	SMA1141C2-2-A
1	SHELL	NOTE 1	NOTE 3	1	SMA5000-1-C
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS				PART NO. SMA1141C23GT50G150		
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED		DATE
				CHECKED		DATE
				DRAWN		DATE
				FILE NO.		

Amphenol

TITLE
SMA CLAMP PLUG

DRAWING NO.
KJ-SMA1141C2-3GT50G-58U-50

ITEM NO