



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. BERYLLIUM COPPER PER QQ-C-530
 4. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-1946B

1. CRIMPED FERRULE
HEX CRIMP SIZE .213"
2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
9	FERRULE	COPPER	NOTE 2	1	FR-648/533X 127C
8	COVER	NOTE 1	NOTE 2	1	SMA1112A3-8-B
7	INSULATOR	PE	NATURAL	1	SMB5090-7
6	RETAINER RING	NOTE 3	NATURAL	1	SMB5000-6
5	CONTACT PIN	NOTE 3	NOTE 4	1	SMB6112A1-5
4	INSULATOR	NOTE 5	NATURAL	1	SMB5090-4T-50
3	BARREL	NOTE 1	NOTE 2	1	SMB5090-3-46/31
2	BODY	NOTE 1	NOTE 2	1	SMB5090-2-A
1	SHELL	NOTE 1	NOTE 2	1	SMB5000-1

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				SMB6112A1-3GT30G-1-50	
				APPROVED	DATE
				10-11-01'	
CHECKED	DATE				
10-11-01'					
DRAWN	DATE				
10-11-01'					
SCALE	5/1	ISSUE	A	FILE NO	

Amphenol

TITLE SMB R/A CRIMP PLUG
(FOR RG-58C/U, 58/U)

DRAWING NO. KJ-SMB6112A1-3GT30G-58U-50

ITEM NO.