



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  3. BERYLLIUM COPPER PER QQ-C-530
  4. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  5. TEFLON MIL-P-19468

1. CRIMPED FERRULE  
HEX CRIMP SIZE .213"
2. CONTACT PIN TO SOLDER

7	FERRULE	COPPER	NOTE 2	1	FR-648/533X 127C
6	CONTACT PIN	NOTE 3	NOTE 4	1	SMB6121A2-6- 125/1
5	SHELL	NOTE 1	NOTE 2	1	SMB5000-1
4	RETAINER RING	NOTE 3	NATURAL	1	SMB5000-6
3	BARREL	NOTE 1	NOTE 2	1	SMB6121A2-3- 46/31
2	INSULATOR	NOTE 5	NATURAL	1	SMB6121A2-2T- 50
1	BODY	NOTE 1	NOTE 2	1	SMB6121A2-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO. SMB6121A2-3GT30G-1-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4			APPROVED	DATE 10-11-01'
			CHECKED	DATE 10-11-01'
			DRAWN	DATE 10-11-01'
SCALE 4/1	ISSUE A	FILE NO		

<b>Amphenol</b>	
TITLE SMB CRIMP PLUG	
DRAWING NO. KJ-SMB6121A2-3GT30G-58U-50	
ITEM NO.	