



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 4. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 5. TEFLON MIL-P-19468

1. MAX. PANEL THICKNESS=2.4mm

					DIMENSIONS ARE IN MILLIMETERS				PART NO. SMC1351B1-3GT30G-50		Amphenol		
					UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED				DATE
5	HEX NUT	NOTE 1	NOTE 3	1	HN635-10-32X15	0.5-6	= ±0.2					TITLE	
4	LOCK WASHER	NOTE 2	NOTE 3	1	LW-78/5X05	6-30	= ±0.4				10-11-01'	SMC BULKHEAD RECEPT. JACK	
3	CONTACT PIN	NOTE 1	NOTE 4	1	SMB7430-3-A	30-120	= ±0.6			CHECKED		DRAWING NO.	
2	INSULATOR	NOTE 5	NATURAL	1	SMB7310-2T-50-A	120-315	= ±1				10-11-01'	KJ-SMC1351B1-3GT30G-50	
1	BODY	NOTE 1	NOTE 3	1	SMC1351B1-1	315-1000	= ±1.6			DRAWN		ITEM NO.	
						1000-2000	= ±2.4				10-11-01'		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	5/1	ISSUE	A	FILE NO			