


Pin strip | Spacing 3.81 mm

STLZ1550/..G-3.81-V-GREEN



Technical Data

Wire sizes		Insulating Material	
Solid min	-	Material	PA 6.6
Solid max	-	Flammability Class	UL 94 V-0
Stranded (flexible) min		Temperatures	
Stranded (flexible) max	-	Operating Temperature	-30 °C - 105 °C
Stranded with Ferrule min	-	Store Temperature	-40 °C - 105 °C
Stranded with Ferrule max	-	Wave Soldering Process	
Dimensions		Soldering Temperature, recommended	265 °C
PCB Hole Diameter	1.2 mm	Peak Soldering Time, recommended	3-4 s
Materials		Reflow Process	
Contact Pin	Copper Alloy	Soldering Temperature, recommended	-
		Peak Soldering Time, recommended	-

Colours


	GREEN, RAL 6018
	BLACK, RAL 9011
	BASALT GREY, RAL 7012
	LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions. Special colours on request.

Counterparts (Spacing 3.81 mm)

Terminal Block				
AKZ1550	AKZ1700	AKZ1710	AKZ4551	AKZ4561

In combination of connectors with different admission data, the lower value is valid.



Ratings

	C ^{RU} US			VDE
UseGroup	B	C	D	
Rated Voltage	300 V	-	300 V	160 V
Rated Current	10 A	-	10 A	10 A
Overvoltage Category				III
Test Voltage	1.60 kV	-	1.60 kV	2.5 kV
Pollution Degree				3

Order Data (Spacing 3.81 mm)

Poles	Width (mm)	Article Designation	Article Number	PU
2	9.01	STLZ1550/2G-3.81-V-GREEN	51550025125 F	200
3	12.82	STLZ1550/3G-3.81-V-GREEN	51550035125 F	200
4	16.63	STLZ1550/4G-3.81-V-GREEN	51550045125 F	200
5	20.44	STLZ1550/5G-3.81-V-GREEN	51550055125 F	200
6	24.25	STLZ1550/6G-3.81-V-GREEN	51550065125 E	100
7	28.06	STLZ1550/7G-3.81-V-GREEN	51550075125 E	100
8	31.87	STLZ1550/8G-3.81-V-GREEN	51550085125 D	50
9	35.68	STLZ1550/9G-3.81-V-GREEN	51550095125 D	50
10	39.49	STLZ1550/10G-3.81-V-GREEN	51550105125 D	50
11	43.30	STLZ1550/11G-3.81-V-GREEN	51550115125 D	50
12	47.11	STLZ1550/12G-3.81-V-GREEN	51550125125 D	50
13	50.92	STLZ1550/13G-3.81-V-GREEN	51550135125 D	50
14	54.73	STLZ1550/14G-3.81-V-GREEN	51550145125 D	50
15	58.54	STLZ1550/15G-3.81-V-GREEN	51550155125 D	50
16	62.35	STLZ1550/16G-3.81-V-GREEN	51550165125 D	50
17	66.16	STLZ1550/17G-3.81-V-GREEN	51550175125 D	50
18	69.97	STLZ1550/18G-3.81-V-GREEN	51550185125 D	50
19	73.78	STLZ1550/19G-3.81-V-GREEN	51550195125 D	50
20	77.59	STLZ1550/20G-3.81-V-GREEN	51550205125 D	50

Accessoires

Figure	Designation	Article Number
	Coding Star CS1-3.5/3.81-RED	Art.-Nr. 5000000023

See pages 282 ff for detail and general accessories and see pages 12/13 concerning services.