

# TP-K01 *Bead Probe*



<b>For Use With</b>	CENTER-300,301,302,303
<b>Applications</b>	Available for general condition, especially for complex and any place hard to reach.
<b>Range</b>	-50°C to 200°C -58°F to 392°F
<b>Tolerances</b>	±2.2°C or ±0.75% (±3.9°F or ±0.75%)
<b>Type</b>	K

# TP-K02 *Immersion Probe*



<b>For Use With</b>	CENTER-300,301,302,303
<b>Applications</b>	Available for temperature measurement of liquid, gels or air
<b>Range</b>	-50°C to 700°C -58°F to 1292°F
<b>Tolerances</b>	±2.2°C or ±0.75% (±3.9°F or ±0.75%)
<b>Type</b>	K

# TP-K03 *Surface Probe*



<b>For Use With</b>	CENTER-300,301,302,303
<b>Applications</b>	Available for flat or curved surface measurement.
<b>Range</b>	-50°C to 400°C -58°F to 752°F
<b>Tolerances</b>	±2.2°C or ±0.75% (±3.9°F or ±0.75%)
<b>Type</b>	K

# **TP-K04** Piercing Probe



<b>For Use With</b>	CENTER-300,301,302,303
<b>Applications</b>	Available for food service, liquids and gels measurement.
<b>Range</b>	-50°C to 600°C -58°F to 1122°F
<b>Tolerances</b>	±2.2°C or ±0.75% (±3.9°F or ±0.75%)
<b>Type</b>	K

# **TP-K05** Surface Probe



<b>For Use With</b>	CENTER-300,301,302,303
<b>Applications</b>	Available for flat or curved surface or hard to reach surface measurement.
<b>Range</b>	-50°C to 400°C -58°F to 752°F
<b>Tolerances</b>	±2.2°C or ±0.75% (±3.9°F or ±0.75%)
<b>Type</b>	K